



**NOTICE**

dB = dB A (SPL) 1m

Tone	[dB]	[dB]
0  110 Hz	107	99
1  3.3 KHZ	106	101
2  3.3 KHZ	110	101
3  3.3 KHZ	110	101
4  970 Hz	95	94
5  2.85 KHZ	99	92
6  1200 Hz	101	93
7  1200 Hz	100	92
8  4.1 KHZ	110	101
9  700 Hz	97	92

Terminal Function:

LED	3	2	1	Function
•	•	•	•	flashing
•	•	•	•	EVS
TONE	4	5	1	Function
•	•	•	•	
•	•	•	•	

Specifications:

12/24VDC/VAC <100mA

Double flash (ON 30ms, OFF 160ms, ON 30ms, OFF 740ms, 1 Hz flash frequency)

or

EVS (Enhanced Visibility System) flashing (random flashing)

Product Selector:

- HS-A : Amber Strobe Dome
- HS-B : Blue Strobe Dome
- HS-C : Clear Strobe Dome
- HS-G : Green Strobe Dome
- HS-R : Red Strobe Dome

**Horn / Strobe Assembly**

**PROPEL ELECTRIC**

**Electrical Diagram**

SIZE / P&ID NO.	DWG. NO.	REV.
	22-0206-01	01

SCALE	SHEET
	1